

Termocoperte ATEX II 3G Bombole Gas

ATEX II 3G Heating Blanket for Gas Bottle



Vista interna
Internal view



Dettaglio chiusura
Closure detail



Prodotto indicato per ottimizzare l'erogazione di GPL in ambito domestico o industriale dove l'importante erogazione di gas tende a gelare il serbatoio.

This product is recommended to optimize the LPG supply in domestic or industrial environments where the important flow of gas tends to freeze the tank.

DATI TECNICI:

- Taglie bombole: 15/20/25kg .
- Alimentazione 230 Vac
- Regolazione temperatura: doppio termostato bimetallico 60°C non regolabile (temperatura raggiunta dalla termocoperta).
- Fusibile di sicurezza 75°C
- Tessuto esterno in fibra di vetro antistatica
- Tessuto aramidico interno
- Coibentazione interna di 1cm in materiale ignifugo
- Strato metallico all'interno collegata a terra
- Cavo alimentazione 3m spina industriale (IEC309)
- Certificazione : **CE** **Ex** II 3G IIB T4

SPECIFICATION:

- Recipient capacity: 15/20/25kg.
- Power supply 230 Vac
- Temperature management: 60°C not adjustable double thermostat (temperature reached by the blanket).
- 75°C Thermal Fuse
- External fabric in antistatic fiber glass
- Internal fabric in aramidic.
- Internal thermal insulation of 1 cm in not flammable material
- Metallic layer connected to ground
- Power cord 3m with industrial plug (IEC 309)
- Certification : **CE** **Ex** II 3G IIB T4

Codice Code	Dimensione Dimension	Potenza Power
TI_GAS.A	100-135 cm x 42 cm	620W